

Центробежные насосы



Центробежный насос NM, NMS Calpeda (Италия), моноблочный, фланцевый

NMM... - однофазный. NM..., NMS... - трехфазный.
Температура жидкости: от -10°C до +90°C.
Температура окружающего воздуха: до +40°C.
Максимальное давление: 10 бар.

Наименование	N, кВт	Q пот, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/DN out	Евро
NMM 32/12F	0,55	12,0	10,0	15,0	12,5	50/32	464
NM 32/12F	0,55	12,0	10,0	15,0	12,5	50/32	446
NMM 32/12D	0,75	12,0	16,0	15,0	18,0	50/32	472
NM 32/12D	0,75	12,0	16,0	15,0	18,0	50/32	472
NMM 32/12A	1,10	12,0	21,0	15,0	23,0	50/32	533
NM 32/12A	1,10	12,0	21,0	15,0	23,0	50/32	510
NM 32/12S	1,50	15,0	20,5	24,0	23,5	50/32	564
NM 32/16A	2,20	13,2	33,0	16,8	35,5	50/32	684
NM 32/20D	2,20	12,0	33,5	13,2	38,0	50/32	740
NM 32/20C	3,00	15,0	38,0	16,8	45,0	50/32	831
NM 32/20A	4,00	15,0	51,5	16,8	57,5	50/32	891
NM 40/12F	1,10	24,0	11,5	30,0	19,0	65/40	538
NM 40/12A	2,20	27,0	19,0	33,0	22,5	65/40	646
NM 40/16B	3,00	24,0	29,0	30,0	31,5	65/40	792
NM 40/16A	4,00	30,0	37,0	33,0	32,5	65/40	925
NM 40/20C	4,00	24,0	39	27,0	44,0	65/40	977
NM 40/20B	5,50	27,0	46	33,0	51,5	65/40	1 330
NM 40/20A	7,50	30,0	52	42,0	59,0	65/40	1 445
NM 40/25C	9,20	24,0	60	33,0	63,5	65/40	2 153
NM 40/25A	15,0	30,0	82	33,0	88,0	65/40	2 648
NM 50/12D	3,00	48,0	15,5	60,0	18,5	65/50	818
NM 50/12A	4,00	54,0	19	66,0	23,5	65/50	931
NM 50/16B	5,50	54,0	25,5	66,0	31,0	65/50	1 303
NM 50/16A	7,50	60,0	30,5	75,0	36,5	65/50	1 412
NM 50/20A	11,0	48,0	50,5	60,0	55,0	65/50	2 198
NM 50/25B	15,0	42,0	66,5	54,0	71,0	65/50	2 691
NM 50/25A	18,5	42,0	82,5	54,0	86,0	65/50	3 290
NM 65/12E	4,00	60,0	16,0	75,0	18,0	80/65	1 016
NM 65/12 A	7,50	66,0	23,5	84,0	26,0	80/65	1 481
NM 65/16 D	7,50	96,0	20,0	120	26,0	80/65	1 502
NM 65/16 B	11,0	96,0	28,0	120	33,5	80/65	2 209
NM 65/20 C	15,0	96,0	37,5	132	44,0	80/65	2 581
NMS 65/250 A	37,0	96,0	90,0	108	83,5	80/65	7 435
NM 80/16 E	7,50	120	16,5	150	20,0	100/80	1 644
NM 80/16 C	11,0	120	24,5	168	27,5	100/80	2 423
NM 80/16 A	18,5	160	30,0	180	38,5	100/80	3 313
NMS 80/200 A	30,0	150	49,5	180	43,0	100/80	5 975
NM 80/250 D	30,0	168	49,0	192	65,0	100/80	6 206
NMS 80/250 A	55,0	180	80,5	192	95,0	100/80	10 563
NM 100/20 D	22,0	180	32,0	270	36,0	125/100	4 625
NMS 100/200 A	45,0	210	56,5	300	61,5	125/100	9 005
NMS 100/250 A	75,0	210	91,0	300	85,0	125/100	14 260

Самовсасывающие насосы



Самовсасывающий насос NGL Calpeda (Италия), резьбовой, эжекторный

Однофазный.
Температура жидкости: от 0°C до +35°C.
Максимальное давление: 8 бар.

Наименование	N, кВт	Q пот, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/DN out	Евро
NGLM 2	0,45	2,0	22	2,3	37,0	25/25	215
NGLM 3	0,55	2,3	28	2,8	53,0	25/25	258
NGLM 4	0,75	4,0	22	4,8	42,0	25/25	280



Самовсасывающий насос NGX Calpeda (Италия), резьбовой, эжекторный

NGXM... - однофазный.
NGX... - трехфазный.
Температура жидкости: от 0°C до +35°C.
Максимальное давление: 8 бар.

Наименование	N, кВт	Q пот, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/DN out	Евро
NGXM 2	0,45	2,0	21	2,4	45,0	25/25	231
NGXM 3	0,55	2,0	30	3,0	53,0	25/25	274
NGXM 5/18	1,10	5,0	27	6,0	50,5	32/25	407
NGX 5/18	1,10	5,0	27	6,0	50,5	32/25	407
NGXM 5/22	1,10	6,0	23	8,4	37,5	32/25	407
NGXM 6/18	1,50	5,0	33	6,0	58,0	32/25	598
NGX 6/18	1,50	5,0	33	6,0	58,0	32/25	598
NGXM 6/22	1,50	6,0	30	8,4	46,5	32/25	598
NGX 6/22	1,50	6,0	30	8,4	46,5	32/25	598



Самовсасывающий многоступенчатый насос MXA Calpeda (Италия), резьбовой, эжекторный

MXAM... - однофазный.
MXA... - трехфазный.
Температура жидкости: от 0°C до +35°C.
Максимальное давление: 8 бар.

Наименование	N, кВт	Q пот, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/DN out	Евро
MXA 205	0,75	4,0	26,5	5,0	55,5	32/25	507
MXA 404	0,75	6,0	22,0	7,0	45,0	25/25	390
MXAM 405	1,10	6,0	31,5	8,0	56,0	32/25	524
MXA 405	1,10	6,0	31,5	8,0	56,0	32/25	524

Многоступенчатые насосы



Многоступенчатый насос CB Stairs Pumps (Тайвань), резьбовой

Однофазный.
Температура жидкости: от 0°C до +90°C.

Наименование	N, кВт	Q пот, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/DN out	Доллар
CBM 2-30	0,47	2,5	19,5	3,5	27,0	25/25	272
CBM 2-40	0,62	2,5	25,3	3,5	37,0	25/25	291
CBM 2-50	0,72	2,5	31,0	3,5	45,0	25/25	336
CBM 2-60	0,83	2,5	38,5	3,5	54,0	25/25	370
CBM 4-30	0,77	5,0	15,5	8,0	26,0	32/25	278
CBM 4-40	0,96	5,0	19,7	8,0	29,0	32/25	311
CBM 4-50	1,16	5,0	28,5	8,0	38,0	32/25	363
CBM 4-60	1,43	5,0	33,0	8,0	46,0	32/25	403
CBM 8-50	1,94	7,0	36,0	10,0	44,0	40/32	608
CBM 8-60	2,09	7,0	42,0	10,0	53,0	40/32	610



Многоступенчатый насос CB Stairs Pumps (Тайвань), резьбовой

Трехфазный.
Температура жидкости: от 0°C до +90°C.

Наименование	N, кВт	Q ном, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/ DN out	Доллар
CB 2-30	0,41	2,5	19,5	3,5	27,0	25/25	263
CB 2-40	0,51	2,5	25,3	3,5	37,0	25/25	282
CB 2-50	0,58	2,5	31,0	3,5	45,0	25/25	323
CB 2-60	0,65	2,5	38,5	3,5	54,0	25/25	355
CB 4-30	0,60	5,0	15,5	8,0	26,0	32/25	269
CB 4-40	0,77	5,0	19,7	8,0	29,0	32/25	296
CB 4-50	0,99	5,0	28,5	8,0	38,0	32/25	350
CB 4-60	1,18	5,0	33,0	8,0	46,0	32/25	390
CB 8-30	1,02	8,0	20,5	10,0	26,0	40/32	389
CB 8-40	1,20	8,0	24,5	11,0	38,0	40/32	412
CB 8-50	1,47	8,0	32,0	11,0	48,5	40/32	447
CB 8-60	1,75	8,0	38,0	11,0	56,0	40/32	645
CB 12-20	0,95	10,0	17,0	14,0	20,5	40/40	363
CB 12-30	1,36	10,0	24,0	14,0	31,0	40/40	414
CB 12-40	1,96	10,0	32,5	14,0	35,0	40/40	583
CB 12-50	2,37	10,0	41,0	14,0	47,0	40/40	692
CB 12-60	2,86	10,0	50,0	14,0	57,0	40/40	810



Многоступенчатый насос MXH Calpeda (Италия), резьбовой

МХНМ... - однофазный. МХН... - трехфазный.
Температура жидкости: от -15°C до +110°C.

Наименование	N, кВт	Q ном, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/ DN out	Евро
МХНМ 202 Е	0,33	3,0	14,2	4,80	22,0	32/25	306
МХН 202 Е	0,33	3,0	14,2	4,80	22,0	32/25	306
МХНМ 203 Е	0,45	3,0	21,7	4,80	33,0	32/25	328
МХН 203 Е	0,45	3,0	21,7	4,80	33,0	32/25	328
МХНМ 204/А	0,55	3,0	30,8	4,80	45,0	32/25	412
МХН 204/А	0,55	3,0	30,8	4,80	45,0	32/25	412
МХНМ 205/А	0,75	3,0	39,0	4,80	57,0	32/25	463
МХН 205/А	0,75	3,0	39,0	4,80	57,0	32/25	463
МХНМ 206В	1,10	3,0	48,0	4,80	68,5	32/25	712
МХН 206В	1,10	3,0	48,0	4,80	68,5	32/25	662
МХНМ 402 Е	0,45	5,0	15,0	8,00	22,5	32/25	350
МХН 402 Е	0,45	5,0	15,0	8,00	22,5	32/25	350
МХНМ 403/А	0,55	5,0	23,0	8,00	33,0	32/25	473
МХН 403/А	0,55	5,0	23,0	8,00	33,0	32/25	473
МХНМ 405 В	1,10	5,0	40,0	8,00	56,5	32/25	668
МХН 405 В	1,10	5,0	40,0	8,00	56,5	32/25	608
МХНМ 406	1,50	5,0	51,0	8,00	68,5	32/25	708
МХН 406	1,50	5,0	51,0	8,00	68,5	32/25	787
МХНМ 803	1,10	8,0	23,0	13,0	36,0	40/25	663
МХН 803	1,10	8,0	23,0	13,0	36,0	40/25	663
МХНМ 804	1,50	8,0	32,0	13,0	48,0	40/25	708
МХН 804	1,50	8,0	32,0	13,0	48,0	40/25	708
МХН 805/А	1,80	8,0	47,0	13,0	60,0	40/25	829
МХН 1602	1,50	14	18,8	25,0	24,0	40/25	616



Многоступенчатый насос XHC Water Technologies (Италия), резьбовой

ХНСМ... - однофазный.
ХНСТ... - трехфазный.
Температура жидкости: до +110°C.

Наименование	N, кВт	Q ном, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/ DN out	Евро
ХНС 2-3М	0,37	2,40	23,0	4,00	27,0	25/25	254
ХНС 2-4М	0,55	2,40	31,0	4,00	36,0	25/25	278
ХНС 2-5М	0,55	2,40	38,0	4,00	44,0	25/25	307
ХНС 2-5Т	0,55	2,40	38,0	4,00	44,0	25/25	307
ХНС 2-6Т	0,75	2,40	44,0	4,00	53,0	25/25	345
ХНС 2-7Т	1,00	2,40	56,0	4,00	64,0	25/25	369
ХНС 4-4Т	0,75	3,50	32,0	6,00	38,0	32/25	307
ХНС 4-5Т	1,00	3,50	41,0	6,00	47,0	32/25	340
ХНС 4-6Т	1,30	3,50	51,0	6,00	56,5	32/25	426
ХНС 4-7Т	1,50	3,50	60,0	6,00	68,0	32/25	441
ХНС 8-25М	1,50	7,00	34,0	10,0	43,0	40/40	450
ХНС 8-30Т	1,85	7,00	40,0	10,0	50,0	40/40	441
ХНС 8-35Т	2,20	7,00	44,0	10,0	56,0	40/40	474
ХНС 8-40Т	2,20	7,00	50,0	10,0	65,0	40/40	484
ХНС 8-50Т	3,00	7,00	62,0	10,0	78,0	40/40	647
ХНС 12-30Т	1,85	12,0	29,5	16,0	35,0	40/40	460
ХНС 16-30Т	2,20	16,0	30,0	24,0	38,0	50/50	472
ХНС 16-40Т	3,00	16,0	40,0	24,0	50,0	50/50	490
ХНС 20-40Т	4,00	20,0	40,0	28,0	50,0	50/50	530



Многоступенчатый насос MXV-B Calpeda (Италия), вертикальный, резьбовой

Трехфазный.
Температура жидкости: от -15°C до +90°C.
Температура окружающего воздуха: до +40°C.
Максимальное давление: 16 бар.

Наименование	N, кВт	Q ном, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/ DN out	Евро
МХV-B 25-203	0,75	3,00	23,5	4,50	34,0	25/25	728
МХV-B 25-204	0,75	3,00	31,0	4,50	44,0	25/25	752
МХV-B 25-205	0,75	3,00	39,0	4,50	56,0	25/25	774
МХV-B 25-206	1,10	3,00	46,5	4,50	68,0	25/25	831
МХV-B 25-207	1,10	3,00	54,5	4,50	79,5	25/25	864
МХV-B 25-208	1,50	3,00	62,0	4,50	91,0	25/25	911
МХV-B 32-403	0,75	5,00	25,0	8,00	34,0	32/32	753
МХV-B 32-404	1,10	5,00	32,5	8,00	45,0	32/32	777
МХV-B 32-405	1,10	5,00	41,0	8,00	56,0	32/32	804
МХV-B 32-406	1,50	5,00	49,5	8,00	68,0	32/32	838
МХV-B 32-407	1,50	10,0	58,0	13,0	79,0	32/32	882
МХV-B 32-408	2,20	5,00	66,0	8,00	91,0	32/32	930
МХV-B 32-410	2,20	5,00	83,0	8,00	114	32/32	984
МХV-B 40-804	1,50	13,0	21,0	11,0	30,0	40/40	824
МХV-B 40-805	2,20	13,0	26,0	11,0	38,0	40/40	865
МХV-B 40-806	2,20	13,0	31,0	11,0	45,0	40/40	918
МХV-B 40-807	3,00	13,0	36,0	11,0	53,0	40/40	1 028
МХV-B 40-808	3,00	13,0	42,0	11,0	60,0	40/40	1 055
МХV-B 40-810	3,70	13,0	52,0	11,0	75,0	40/40	1 206



Многоступенчатый насос MXV Calpeda (Италия), вертикальный, фланцевый

Трехфазный.
Температура жидкости: от -15°C до +90°C.
Температура окружающего воздуха: до +40°C.
Максимальное давление: 16 бар.

Наименование	N, кВт	Q ном, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/ DN out	Евро
MXV 50-1603	3,00	15,0	42,50	24,0	51,0	50/50	1 360
MXV 50-1604	4,00	15,0	57,00	24,0	69,0	50/50	1 393
MXV 50-1605	5,50	15,0	71,00	24,0	86,0	50/50	1 665
MXV 50-1606	5,50	15,0	85,50	24,0	100	50/50	2 273
MXV 50-1607	7,50	15,0	100,0	24,0	120	50/50	2 350
MXV 50-1608	7,50	15,0	113,5	24,0	130	50/50	2 422
MXV 65-3202	4,00	28,5	29,50	44,0	37,0	65/65	2 202
MXV 65-3203	5,50	28,5	44,75	44,0	55,0	65/65	2 891
MXV 65-3204	7,50	28,5	59,75	44,0	75,0	65/65	3 249
MXV 65-3205	11,0	28,5	75,00	44,0	93,5	65/65	4 071
MXV 65-3206	11,0	28,5	89,50	44,0	105	65/65	4 481
MXV 65-3207	15,0	28,5	102,5	44,0	131	65/65	5 646
MXV 65-3208	15,0	28,5	119,5	44,0	139	65/65	5 909
MXV 80-4802	5,50	42,5	28,00	60,0	40,0	80/80	2 828
MXV 80-4803	7,50	42,5	42,00	60,0	61,0	80/80	3 327
MXV 80-4804	11,0	42,5	67,50	60,0	80,0	80/80	4 211
MXV 80-4805	15,0	42,5	71,75	60,0	101	80/80	4 599
MXV 80-4806	15,0	42,5	86,00	60,0	120	80/80	5 368
MXV 80-4807	18,5	42,5	101,5	60,0	142	80/80	6 278
MXV 80-4808	22,0	42,5	114,5	60,0	162	80/80	7 180
MXV 100-6501	5,50	49,5	23,00	85,0	25,0	100/100	3 124
MXV 100-6502-2R	7,50	49,5	34,00	85,0	37,5	100/100	3 740
MXV 100-6502	11,0	49,5	47,00	85,0	51,0	100/100	4 482
MXV 100-6503-2R	15,0	49,5	58,00	85,0	63,5	100/100	5 431
MXV 100-6503	18,5	49,5	70,25	85,0	76,0	100/100	5 697
MXV 100-6504-2R	18,5	49,5	81,00	85,0	88,5	100/100	6 059
MXV 100-6504	22,0	49,5	94,50	85,0	102	100/100	6 712
MXV 100-6505-2R	30,0	49,5	106,5	85,0	116	100/100	9 613
MXV 100-6505	30,0	49,5	118,5	85,0	129	100/100	9 613



Многоступенчатый насос VSC Stairs Pumps (Тайвань), вертикальный, фланцевый

Трехфазный.
Температура жидкости: от -15°C до +120°C.

Наименование	N, кВт	Q ном, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/ DN out	Доллар
VSC 1-4	0,37	1,8	18,0	2,4	22,0	32/32	504
VSC 1-6	0,37	1,8	27,0	2,4	35,0	32/32	545
VSC 1-8	0,55	1,8	37,0	2,4	48,0	32/32	593
VSC 1-10	0,55	1,8	45,0	2,4	59,0	32/32	644
VSC 1-23	1,10	1,8	100,0	2,4	133,0	32/32	947
VSC 3-6	0,55	3,0	27,0	4,5	38,0	32/32	552
VSC 3-8	0,75	3,0	37,0	4,5	50,0	32/32	616
VSC 3-10	0,75	3,0	45,0	4,5	63,0	32/32	667
VSC 3-12	1,10	3,0	55,0	4,5	75,0	32/32	722
VSC 3-15	1,10	3,0	68,0	4,5	96,0	32/32	780
VSC 3-19	1,50	3,0	90,0	4,5	123,0	32/32	993
VSC 3-25	2,20	3,0	120,0	4,5	155,0	32/32	1 156
VSC 5-6	1,10	6,0	25,0	8,5	38,0	32/32	608
VSC 5-7	1,10	6,0	30,0	8,5	42,0	32/32	631

Наименование	N, кВт	Q ном, м³/ч	H ном, м	Q max, м³/ч	H max, м	DN in/ DN out	Евро
VSC 5-8	1,10	6,0	34,0	8,5	51,0	32/32	666
VSC 5-9	1,50	6,0	41,0	8,5	59,0	32/32	827
VSC 5-10	1,50	6,0	46,0	8,5	65,0	32/32	850
VSC 5-11	2,20	6,0	52,0	8,5	72,0	32/32	907
VSC 5-13	2,20	6,0	62,0	8,5	86,0	32/32	965
VSC 5-15	2,20	6,0	71,0	8,5	100,0	32/32	1 010
VSC 5-18	3,00	6,0	88,0	8,5	120,0	32/32	1 215
VSC 5-24	4,00	6,0	120,0	8,5	155,0	32/32	1 458
VSC 10-3	1,10	10,0	21,0	13,0	30,0	40/40	726
VSC 10-4	1,50	10,0	30,0	13,0	38,0	40/40	896
VSC 10-5	2,20	10,0	39,0	13,0	50,0	40/40	971
VSC 10-6	2,20	10,0	46,0	13,0	60,0	40/40	1 012
VSC 10-7	3,00	10,0	57,0	13,0	70,0	40/40	1 187
VSC 10-8	3,00	10,0	62,0	13,0	80,0	40/40	1 229
VSC 15-2	2,20	17,0	20,0	23,5	27,0	50/50	928
VSC 15-3	3,00	17,0	30,0	23,5	40,0	50/50	1 127
VSC 15-4	4,00	17,0	42,0	23,5	52,0	50/50	1 288
VSC 15-5	4,00	17,0	53,0	23,5	67,0	50/50	1 356
VSC 15-6	5,50	17,0	65,0	23,5	82,0	50/50	1 758
VSC 20-3	4,00	20,0	32,0	29,0	43,0	50/50	1 220
VSC 20-4	5,50	20,0	45,0	29,0	55,0	50/50	1 624
VSC 20-5	5,50	20,0	58,0	29,0	68,0	50/50	1 692
VSC 20-6	7,50	20,0	70,0	29,0	82,0	50/50	1 850
VSC 20-7	7,50	20,0	82,0	29,0	99,0	50/50	1 942
VSC 32-3	5,50	32,0	40,0	40,0	58,0	65/65	2 135
VSC 32-4-2	7,50	32,0	49,0	40,0	70,0	65/65	2 424
VSC 32-4	7,50	32,0	53,0	40,0	78,0	65/65	2 422
VSC 32-5	11,00	32,0	71,0	40,0	98,0	65/65	3 160
VSC 32-6	11,00	32,0	85,0	40,0	118,0	65/65	3 311
VSC 45-2-2	5,50	45,0	30,0	58,0	40,0	80/80	2 173
VSC 45-2	7,50	45,0	38,0	58,0	50,0	80/80	2 307
VSC 45-3	11,00	45,0	58,0	58,0	78,0	80/80	3 173
VSC 45-4	15,00	45,0	78,0	58,0	98,0	80/80	3 471
VSC 64-2-2	7,50	60,0	30,0	85,0	40,0	100/100	2 440
VSC 64-2	11,00	60,0	45,0	85,0	60,0	100/100	3 045
VSC 64-3	18,50	60,0	70,0	85,0	89,0	100/100	3 943
VSC 64-4-1	22,00	60,0	87,0	85,0	108,0	100/100	4 553
VSC 64-4	22,00	60,0	93,0	85,0	118,0	100/100	4 551
VSC 90-2	15,00	80,0	46,0	120,0	68,0	100/100	3 444
VSC 90-3	22,00	80,0	70,0	120,0	102,0	100/100	4 706